



R-T表

广东爱晟电子科技有限公司

R25	10(KΩ)	阻值精度	1.0%	型号: DT103F3470A			
B25/50	3470K	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
-40	212.740	221.651	230.913	3	24.3895	24.8613	25.3396
-39	200.738	209.024	217.631	4	23.3453	23.7863	24.2333
-38	189.495	197.202	205.202	5	22.3521	22.7644	23.1820
-37	178.958	186.129	193.568	6	21.4072	21.7925	22.1826
-36	169.078	175.752	182.671	7	20.5079	20.8680	21.2323
-35	159.809	166.023	172.461	8	19.6518	19.9882	20.3284
-34	151.111	156.898	162.890	9	18.8365	19.1508	19.4684
-33	142.944	148.334	153.913	10	18.0599	18.3534	18.6498
-32	135.272	140.295	145.490	11	17.3199	17.5940	17.8706
-31	128.062	132.744	137.584	12	16.6146	16.8704	17.1285
-30	121.284	125.649	130.159	13	15.9422	16.1809	16.4215
-29	114.909	118.980	123.183	14	15.3009	15.5235	15.7479
-28	108.910	112.708	116.626	15	14.6891	14.8968	15.1058
-27	103.264	106.807	110.460	16	14.1054	14.2989	14.4937
-26	97.946	101.253	104.660	17	13.5483	13.7285	13.9098
-25	92.936	96.023	99.202	18	13.0163	13.1842	13.3529
-24	88.215	91.096	94.063	19	12.5083	12.6646	12.8215
-23	83.763	86.454	89.223	20	12.0231	12.1684	12.3142
-22	79.564	82.078	84.662	21	11.5594	11.6945	11.8299
-21	75.602	77.950	80.363	22	11.1163	11.2417	11.3674
-20	71.862	74.056	76.309	23	10.6926	10.8090	10.9256
-19	68.334	70.384	72.489	24	10.2875	10.3954	10.5035
-18	65.000	66.916	68.883	25	9.9000	10.0000	10.1000
-17	61.849	63.641	65.478	26	9.5219	9.6218	9.7218
-16	58.871	60.546	62.263	27	9.1604	9.2600	9.3598
-15	56.054	57.620	59.225	28	8.8146	8.9139	9.0134
-14	53.389	54.854	56.353	29	8.4838	8.5826	8.6817
-13	50.866	52.237	53.638	30	8.1672	8.2654	8.3640
-12	48.478	49.760	51.070	31	7.8641	7.9617	8.0597
-11	46.216	47.415	48.641	32	7.5740	7.6708	7.7681
-10	44.074	45.195	46.341	33	7.2961	7.3921	7.4886
-9	42.043	43.092	44.164	34	7.0300	7.1251	7.2208
-8	40.118	41.100	42.102	35	6.7750	6.8691	6.9639
-7	38.292	39.211	40.148	36	6.5306	6.6238	6.7176
-6	36.560	37.420	38.296	37	6.2963	6.3885	6.4813
-5	34.916	35.721	36.540	38	6.0717	6.1628	6.2546
-4	33.356	34.109	34.875	39	5.8563	5.9463	6.0371
-3	31.874	32.579	33.295	40	5.6497	5.7386	5.8282
-2	30.467	31.126	31.796	41	5.4515	5.5392	5.6277
-1	29.130	29.747	30.373	42	5.2612	5.3478	5.4351
0	27.859	28.436	29.022	43	5.0786	5.1640	5.2502
1	26.643	27.183	27.731	44	4.9033	4.9874	5.0725
2	25.488	25.992	26.504	45	4.7350	4.8179	4.9017



R-T表

广东爱晟电子科技有限公司

R25(KΩ)	10	阻值精度	1.0%	型号: DT103F3470A			
B25/50	3470	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
46	4.5733	4.6550	4.7376	89	1.2024	1.2402	1.2790
47	4.4180	4.4984	4.5798	90	1.1694	1.2064	1.2445
48	4.2687	4.3479	4.4281	91	1.1374	1.1737	1.2111
49	4.1253	4.2032	4.2822	92	1.1064	1.1421	1.1788
50	3.9874	4.0641	4.1419	93	1.0763	1.1114	1.1474
51	3.8548	3.9303	4.0069	94	1.0473	1.0816	1.1170
52	3.7274	3.8016	3.8769	95	1.0191	1.0528	1.0876
53	3.6047	3.6777	3.7519	96	0.9918	1.0249	1.0590
54	3.4868	3.5586	3.6315	97	0.9654	0.9979	1.0314
55	3.3732	3.4438	3.5155	98	0.9398	0.9717	1.0045
56	3.2640	3.3334	3.4039	99	0.9150	0.9462	0.9785
57	3.1588	3.2270	3.2964	100	0.8909	0.9216	0.9533
58	3.0576	3.1246	3.1928	101	0.8676	0.8977	0.9288
59	2.9601	3.0259	3.0929	102	0.8449	0.8745	0.9050
60	2.8661	2.9308	2.9967	103	0.8230	0.8520	0.8820
61	2.7757	2.8392	2.9039	104	0.8017	0.8302	0.8597
62	2.6885	2.7509	2.8145	105	0.7811	0.8091	0.8380
63	2.6045	2.6658	2.7283	106	0.7611	0.7885	0.8169
64	2.5235	2.5837	2.6451	107	0.7416	0.7686	0.7965
65	2.4454	2.5046	2.5649	108	0.7228	0.7493	0.7766
66	2.3702	2.4282	2.4875	109	0.7045	0.7305	0.7573
67	2.2976	2.3546	2.4128	110	0.6867	0.7122	0.7386
68	2.2275	2.2835	2.3407	111	0.6695	0.6945	0.7205
69	2.1600	2.2149	2.2711	112	0.6528	0.6774	0.7028
70	2.0948	2.1488	2.2039	113	0.6365	0.6607	0.6857
71	2.0319	2.0849	2.1390	114	0.6208	0.6445	0.6690
72	1.9712	2.0232	2.0763	115	0.6054	0.6287	0.6528
73	1.9126	1.9636	2.0158	116	0.5906	0.6134	0.6371
74	1.8560	1.9061	1.9573	117	0.5761	0.5985	0.6218
75	1.8013	1.8505	1.9008	118	0.5621	0.5841	0.6069
76	1.7485	1.7968	1.8461	119	0.5484	0.5701	0.5925
77	1.6975	1.7449	1.7934	120	0.5352	0.5564	0.5784
78	1.6482	1.6947	1.7423	121	0.5223	0.5431	0.5648
79	1.6006	1.6462	1.6930	122	0.5097	0.5302	0.5515
80	1.5546	1.5994	1.6452	123	0.4976	0.5177	0.5386
81	1.5100	1.5540	1.5990	124	0.4857	0.5055	0.5260
82	1.4670	1.5101	1.5543	125	0.4742	0.4936	0.5138
83	1.4253	1.4676	1.5110	126	0.4630	0.4821	0.5019
84	1.3850	1.4265	1.4691	127	0.4521	0.4709	0.4903
85	1.3461	1.3868	1.4286	128	0.4416	0.4600	0.4791
86	1.3084	1.3483	1.3894	129	0.4313	0.4493	0.4681
87	1.2719	1.3111	1.3514	130	0.4212	0.4390	0.4575
88	1.2366	1.2751	1.3146	131	0.4115	0.4289	0.4471

